

## Versions, Sizes & Installation Suggestions

Choose from 3 versions of FloorAppeal:  
**Low-Tac, High-Tac or High-Tac EX**

**LOW-TAC** optimally designed for all smooth indoor surfaces such as wooden platforms, metal, plastic laminate, linoleum, tile & carpeting.

use with: Solvent, UV & Latex inks.

**Available Roll Sizes:** 54" x 50' • 54" x 100'

**HIGH-TAC** most suitable for outdoor surfaces like, very smooth concrete, cement, certain types of brick, untreated natural stone & plush/shag carpeting.

use with: Solvent, UV & Latex inks.

**Available Roll Sizes:** 54" x 50' • 54" x 100'

**HIGH-TAC EX** Most suitable for outdoor surfaces like aging concrete, asphalt & brick for building wraps.

use with: Solvent, UV & Latex inks.

**Available Roll Sizes:** 54" x 100'

### INSTALLATION SUGGESTIONS

- Surface must be completely dry and free from water, grease, oil stains, road salts, acids, sand & pebbles before installing the product. (if surface isn't clean & dry, the adhesive performance will be inhibited)

**KEEP IN MIND:** the material **can not** be exposed to any elements (rain, snow, soap, etc.) for at least 24 hours after installation, as any exposure will inhibit adhesive performance.

- Initially apply the material by hand. (using an applicator roller will help ensure the material conforms to whatever surface it is being applied to)
- Force all air bubbles out to ensure the material is completely adhered to the surface
- FloorAppeal works best when applied edge to edge with no overlapping

**PRO TIP:** tap edges of material with a rubber mallet or use a roller to help with sealing the graphic to the surface.



### CLEANING

- When cleaning FloorAppeal products start in the middle and work your way out.

(cleaning from the edges toward the middle of the product may damage the adhesive properties of the product.)

**NOTE:** If power washing, use low pressure and keep at least 3½ feet away from the product

### REMOVING

- Using a putty knife or razor, peel the material off at less than a 45° angle.

**NOTE:** FloorAppeal is easiest to remove under warm conditions

Disclaimer: There are some conditions which are beyond the manufacturer's control. The user is responsible for determining the products suitability including adhesion and removal characteristics. No legal responsibility can be claimed to the manufacturer or distributor.

Please contact **Infinity Media Company** via phone 1 (708) 352-1086 or by email (Russ@inmediaco.com) to request a free sample roll, sample folder or an authorized dealer near you.

-www.FloorAppeal.net-