



INFINITY

MEDIA COMPANY

5350 East Avenue • Countryside, IL 60525

CERTIFICATE OF ANALYSIS FLOORAPPEAL LOW-TAC, HIGH-TAC & HIGH-TAC EX

PRODUCT INFORMATION

FloorAppeal Low-Tac, FloorAppeal High-Tac & FloorAppeal High-Tac EX

Material: Fabric Polyester

Core Size: 3"

GENERAL PROPERTIES

PROPERTY	UNIT	SPEC	VALUE	TEST METHOD
Appearance	-	White		ASTM E284
Base Thickness	μm	360 ± 50		ASTM D645
Total Thickness	μm	510 ± 50		ASTM D646
Base Weight	g/m ²	240 ± 20		ASTM D646
Total Weight	g/m ²	390 ± 20		ASTM D646
Gloss	%	60° : White 7% ± 3%	Pass	ASTM D2457
Pin Hole	-	Size : 5.0 mm ≥ 3 ea ≥		Square
Dust	-	Size : 5.0 mm ≥ 3 ea ≥		Square

ADHESION PROPERTIES

PROPERTY	UNIT	Low-Tac	High-Tac	High-Tac EX	TEST METHOD
Adhesive (gf/in)	/	Low-Tac	High-Tac	High-Tac EX	ASTM D 3330
	20 Min	800 ± 100	1000 ± 100	1200 ± 100	
	1 HR	850 ± 100	1100 ± 100	1550 ± 100	
	24 HR	900 ± 100	1400 ± 100	1800 ± 100	

Thickness of Material & Liner is 15 Mil • 240 GSM
Material is 10 mil • Liner is 5 mil

Infinity Media Company is not responsible for the information provided.

Infinity Media Company • 5350 East Avenue Countryside, IL 60525 • info@floorappeal.net • 1 (708) 352-1086